

Weller®	Plato® Tip	Tip drawings are actual size.
ETA	EW-303	
ETB	EW-305	
ETC	EW-307	
ETD	EW-103	
ETE	EW-105	
ETGW	EW-0574	 SMD Flow Tip
ETH	EW-301	
ETJ	EW-302	
ETK	EW-304	
ETL	EW-306	
ETM	EW-308	

Weller®	Plato® Tip	Tip drawings are actual size.
ETD	EW-404	
ETP	EW-403	
ETR	EW-101	
ETW	EW-4796	
ETS	EW-402	
ETT	EW-401	
ETV	EW-511	
ETX	EW-0602	 SMD
ETAA	EW-513	
ETBB	EW-515	
ETCC	EW-517	

NEW!
LONG LIFE TIPS TO REPLACE WELLER'S LT SERIES TIPS

- Longer Life
- Designed for lead-free soldering
- Look for tips with an LF added to the end of the part number

Weller®	Plato® Tip	Tip drawings are actual size.		Weller®	Plato® Tip	Tip drawings are actual size.	
—	MS-4140		.031" (0.8)	LTD LF	MS-3600 LF		.181" (4.6)
LT1	MS-4120		.010" (0.25)	LTGW	MS-0100		.122" (3.1) / .084" (2.1)
LT1L	MS-4110		.010" (0.25)	LTGW LF	MS-0100 LF		.122" (3.1) / .084" (2.1)
LT1LX	MS-4101		.010" (0.25)	LTH	MS-3110		.031" (0.8)
LT1S	MS-4100		.063" (1.6)	LTHX	MS-3101		.024" (0.6)
LT4W	MS-5160		.047" (1.2)	LTK	MS-3150		.050" (1.3)
LT4X	MS-3125		0.085 (2.1) / 0.047 (1.2)	LTL	MS-3250		.079" (2.0)
LTA	MS-3200		.063" (1.6)	LTM	MS-3450		.125" (3.2)
LTA LF	MS-3200 LF		.063" (1.6)	LTS	MS-4130		.018" (0.5)
LTB	MS-3300		.094" (2.4)	LTO LF	MS-4200 LF		.039" (0.9)
LTB LF	MS-3300 LF		.094" (2.4)	LTBB LF	MS-5300 LF		.094" (2.4)
LTC	MS-3400		.125" (3.2)	LTCC LF	MS-5400 LF		.125" (3.2)
LTC LF	MS-3400 LF		.125" (3.2)	LTKN LF	MS-0201-LF		0.162" (4.0) / 0.002" (0.05) / 0.06" (1.5)
LTD	MS-3600		.181" (4.6)				

Be sure to add temperature indicating number to Plato® part number when ordering Plato® C-Tips.

Choose the desired temperature and add it to the end of the Plato part number* (Example C-3039-7)

Desired Temperature	Suffix to Add to Plato Part Number
700°F / 370°C	-7
800°F / 425°C	-8
900°F / 480°C	-9

Weller®	Plato® Tip	Tip drawings are actual size.
PTA	C-3039	
PTB	C-3040	
PTC	C-3036	
PTD	C-1016	
PTE	C-1017	
PTF	C-593	
PTH	C-3100	
PTJ	C-3865	
PTK	C-3043	
PTL	C-3044	
PTM	C-3102	
PTD	C-4223	

Weller®	Plato® Tip	Tip drawings are actual size.
PTP	C-462	
PTR	C-1021	
---	C-4794	
PTS	C-494	
PTT	C-4309	
PTAA	C-5139	
PTBB	C-5143	
PTCC	C-5141	
PTDD	C-5142	

* Indicated temperature ranges are nominal and will vary according to style of tip, condition of iron, manner of use, and other variables. All dimensions are shown before tinning and are subject to manufacturing tolerances.

All points are 1/32" (0.8) thick unless otherwise noted. Tip samples available. () = mm

Weller® Plato® Tip

Tip drawings are actual size.



Micro Soldering Pencil • MLR 20 • MPR 30

Weller® Plato® Tip


Tip drawings are actual size.



Soldering Iron • W100PG

Weller® Plato® Tip

Tip drawings are actual size.



Pace®

Plato® Tip


Tip drawings are actual size.

1121-0335	33-6055	1/16" (1.5)	
1121-0336	33-8142	1/32" (0.8)	
1121-0337	33-6058	1/8" (3.2)	
1121-0357	33-8141	1/64" (0.4)	
1121-0358	33-1658	3/16" (4.8)	
1121-0359	33-1144	1/32" (0.8)	
1121-0360	33-6057	3/32" (2.4)	
1121-0361	33-1146	.020" (0.5)	
1121-0363	33-8143	.020" (0.5)	
1121-0402	SMP-2004	3/16" (4.7)	 SMD Blade Tip to Solder SOIC & PLCC's
1121-0406	33-5894	1/8" (3.2)	
1121-0414	33-6056	1/16" (1.5)	
1121-0490	33-5895	.195" (5.0)	 Plato® SMD Flow Tip
1121-0499	33-1147	1/16" (1.5)	
1121-0516	33-3981	.015" (0.4)	
1121-0526	33-3982	.015" (0.4)	
1121-0531	33-7106	.187" (4.8)	
1121-0532	33-7107	.125" (3.2)	
1121-0533	33-7103	.062" (1.6)	

Desoldering Tips to Replace Pace Endura Tips

Desoldering Irons SX90, SX-80 and SX-70 with Paper Chamber 3/16" Diameter

PACE®

Pace®	Plato®	ID	OD			
1121-0625	30-0301	.030"	.080"	NEW!		
1121-0624	30-0401	.040"	.090"			
1121-0626	30-0601	.060"	.120"	NEW!		
1121-0627	30-0901	.090"	.200"			
1121-0628	30-1003	.030"	.090"	NEW!		
1121-0629	30-1004	.040"	.10"			
1121-0630	30-1006	.060"	.120"	NEW!		
1121-0681	30-1020	.020"	.070"			
1121-0682	30-1030	.030"	.080"	NEW!		
1121-0683	30-1040	.040"	.090"			
1121-0631	30-1060	.060"	.185"	NEW!		
1121-0680	30-1200	.020"	.070"			
1121-0678	30-1300	.030"	.080"	NEW!		
1121-0679	30-1400	.040"	.090"			
1121-0690	30-1600	.060"	.110"	NEW!		

Desoldering Irons SX90, SX-80 and SX-70 with Glass Chamber 3/16" Diameter

PACE®

Pace®	Plato®	(mm)			
		D1	D2		
1121-0367	30-0300	.030"	.065"		
		(0.8)	(1.7)		
1121-0342	30-0400	.040"	.085"		
		(1.0)	(2.2)		
1121-0463	30-040	.040"	.065"		
		(1.0)	(2.2)		
---	30-050	.050"	.095"		
		(1.3)	(2.4)		
1121-0368	30-0600	.060"	.115"		
		(1.5)	(2.9)		
1121-0464	30-060	.060"	.115"		
		(1.5)	(2.9)		
1121-0507	30-0900	.090"	.190"		
		(2.3)	(4.8)		

Tip drawing is actual size.

Desoldering Irons • Pace® • Air-Vac® • A.P.E.

AIR-VAC®

A.P.E.®

PACE®

Pace®	Plato®	L	D1	D2
Plato® Tips to fit Pace® SX-20, SX-25, SX-25V SODR-X-TRACTORS®				
1121-0480	20-0114	1.00" (25.4)	.030" (0.8)	.060" (1.5)
---	20-0815	1.00" (25.4)	.036" (0.9)	.065" (1.7)
1121-0479	20-0110	1.00" (25.4)	.040" (1.0)	.080" (2.0)
1121-0216	20-0113	1.00" (25.4)	.050" (1.3)	.090" (2.3)
1121-0217	20-0111	1.00" (25.4)	.050" (1.5)	.100" (2.5)



Pace®	Plato®	L	D1	D2
Plato® Tips to fit Pace® SX-40A, SX-55A, SX-65A, SX-70 SODR-X-TRACTORS® with Plato Adapter 33-0001				
1121-0485	20-025	1.75" (44.5)	.030" (0.8)	.080" (2.0)
1121-0486	20-040	1.75" (44.5)	.040" (1.0)	.080" (2.0)
---	20-050	1.75" (44.5)	.050" (1.3)	.090" (2.3)
1121-0255	20-060	1.75" (44.5)	.060" (1.5)	.100" (2.5)